



Multi-Purpose Bearing Grease



FEATURES

- Ideal for lubricating all types of bearings
- Extends relubrication periods
- Prolongs bearing life
- Excellent load carrying properties
- Good corrosion resistance
- Reduces grease consumption

APPLICATIONS

- Cement Mixers
- Conveyors
- Elevators
- Gas Extractors
- Motors
- Tray Loaders
- Ventilator Fans

PROPERTIES

Color	Blue.
Appearance / Physical State	Solid.
Odor	Not available.
Melting / Freezing Point	Not available.
Boiling Point / Range	640.4°F (338°C)
Flash Point	471.2°F (244.0°C)
Evaporation Rate	Not available.
Vapor Pressure	Not applicable.
Vapor Density	Not applicable.
Density	0.89513 g/cm ³ (7.46986 lbs/gal) (relative density)
Water Solubility	Not available.
Auto-Ignition Temperature	Not available.
Viscosity	140-170 cSt @ 40°C 14 cSt @ 100°C
NLGI Grade	2
Thickener Type	Lithium Complex
Base Oil Type	Mineral Oil
VOC Content	0%
Dropping Point	>500°F
4-Ball Weld Load	315 kg
Timken OK Load	50 lb
Temperature Range	-10°F (-23°C) to 350°F (177°C)
Copper Corrosion	1B

DIRECTIONS

For use as a high performance, multi-functional bearing grease. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

HANDLING

Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
70614	C70614	14.1 oz / 400 g	cartridge	30	32 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved