



All-Purpose Foaming Cleaner

FEATURES

- Designed to remove grease and soil
- Clinging foam permits long lasting contact with surfaces to be cleaned
- Use to clean countertops, walls, cabinets, and greasy parts

APPLICATIONS

- Plastic
- Ceramic
- Concrete
- Metal
- Urethane
- and more

DIRECTIONS

Spray evenly over surface. Wipe clean or spray with clean water. For heavily soiled surfaces, have product remain on surface for an extended period of time.

HANDLING

Shake well before using. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

STORAGE

Protect from sunlight. Store in a well-ventilated place. May explode if heated. KEEP OUT OF REACH OF CHILDREN.

DISPOSAL

Dispose of contents/container according to local/national disposal regulations.



PROPERTIES

Appearance / Physical State	Gas.
Color	Clear to Light Yellow.
Odor	Lemon.
pH Value	11.5
Flash Point	Not available.
Evaporation Rate	Not available.
Flammability	Not available.
Vapor Pressure	Not available.
Vapor density	> 1 (Air=1)
Water Solubility	Complete.
Auto-Ignition Temperature	Not available.
Viscosity	Not available.
Density	8.45 lb/gal
Specific Gravity	1.012
VOC Content	7.99 % per US State & Federal Consumer Product Regulations
Propellant	Petroleum Gases (CAS 68476-86-8)

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
19220	18 oz / 510 g	aerosol	12	18 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved