



LPS[®] DETEX[®] Belt Dressing



FEATURES

- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Prevents belt slippage and squeaks on all belt types
- Withstands frequent washdowns, extending maintenance cycles and reducing downtime
- Contains no chlorinated solvents that deteriorate drive belts
- May be used indoors or in wet/outdoor conditions
- Metal and X-ray detectable packaging

APPLICATIONS

- Appliance Drive Belts
- Bushings
- Flat Belts
- Polishing Belts
- Round Belts

SPECIFICATIONS AND APPROVALS

- NSF International, H1 (Aerosol)
- Halal Product Certified #HP-5543-CH
- Ford Motor Co.

PROPERTIES

Appearance / Physical State	Gas
Color	Clear. Colorless.
Odor	Hydrocarbon-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	195.8°F (91°C) (concentrate)
Flash Point	19.4°F (-7.0°C) Tag Closed Cup
Evaporation Rate	> 1 BuAc
Flammability	lower: 0.6%; upper: 7%
Vapor Pressure	Not available.
Partition Coefficient	Not available.
Vapor Density	Not available.
Auto-Ignition Temperature	Not available.
Viscosity	Not available.
Density	5.74 lb/gal
Percent volatile	90%
Specific Gravity	0.67 - 0.69 @ 20°C
VOC Content	90%
Propellant	Propane/Butane
Temperature Range	32°F (0°C) to 325°F (163°C)

DIRECTIONS

Turn off equipment and stop belts before applying. Spray inner surface of belt from 6 to 8 inches. Use only enough to cover belt. Let vapors dissipate. Repeat as needed. Avoid contamination of food in the application and storage of the product.

HANDLING

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection. Wash thoroughly after handling. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Store locked up.

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
02216	C02216	10 wt oz / 284 g / 433 mL	aerosol	12	11 lbs

METAL DETECTION DETAILS

1. Detection limits for a particular machine depend on a variety of factors including line speed, contaminant placement and orientation, iron fortification (i.e.; flour), wet mode vs. dry mode, fragment size, aperture size, etc. It is the responsibility of the end- user to determine the detection limits of the appropriate DETEX[®] component for the individual line set up and for the particular food product being inspected.
2. Metal and X-ray detection limits for plastic components (above) are based on whole components. Partial plastic and scouring pad components may not be detectable due to detector limitations, partial component size, malfunctioning equipment and/or the type of food product undergoing processing. Scouring pad not X-ray detectable.
3. ITW Pro Brands recommends that all components be tested prior to implementation (separately and included in the processed food product) and/or consult your specific metal detector equipment manufacturer directly.
4. Product shelf life, warranty, and material safety data sheets are available at www.itwprobrands.com. ITW Pro Brands is not responsible for use of this product inconsistent with its instructions and warnings.
5. ITW Pro Brands is not responsible for failure to detect components due to detector limitations and/or detector malfunctions. Refer to the metal detector manufacturer's design limitations, instructions, and warnings regarding the use, limitations, and proper maintenance of the equipment.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved