



# **FEATURES**

- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Versatile grease engineered for the lubrication of ball, roller, and other bearings
- NLGI #2 grease effectively lubricates bearing while providing excellent corrosion protection
- Withstands frequent washdowns, extending maintenance cycles and reducing downtime
  Matel and X regulaterations and
- Metal and X-ray detectable cap

## APPLICATIONS

- Bearings
- Chains
- Channels
- Conveyors

- Food RacksFood Service Carts
- Gears
  - Open Drives

# SPECIFICATIONS AND APPROVALS

 Halal Product Certified #HP-5543-CH

Filling Equipment

NSF International, H1

## PROPERTIES

Appearance / Physical State   Solid. Paste.     Color   White     Odor   Hydrocarbon-like.     Melting / Freezing Point   Not established.     Boiling Point / Range   Not available.     Flash Point   400.0 °F (204.4 °C) Tag Close Cup     Evaporation Rate   < 1 (BuAc = 1)	d		
Odor   Hydrocarbon-like.     Melting / Freezing Point   Not established.     Boiling Point / Range   Not available.     Flash Point   400.0 °F (204.4 °C) Tag Close Cup     Evaporation Rate   < 1 (BuAc = 1)     Vapor Pressure   Not established.     Vapor density   < 1 (air = 1)     Specific Gravity   0.87 @ 15°C     Water Solubility   Not soluble.     Partition Coefficient   >1	d		
Melting / Freezing Point   Not established.     Boiling Point / Range   Not available.     Flash Point   400.0 °F (204.4 °C) Tag Close Cup     Evaporation Rate   < 1 (BuAc = 1)	d		
Boiling Point / Range   Not available.     Flash Point   400.0 °F (204.4 °C) Tag Close Cup     Evaporation Rate   < 1 (BuAc = 1)     Vapor Pressure   Not established.     Vapor density   < 1 (air = 1)     Specific Gravity   0.87 @ 15°C     Water Solubility   Not soluble.     Partition Coefficient   >1	d		
Flash Point   400.0 °F (204.4 °C) Tag Close Cup     Evaporation Rate   < 1 (BuAc = 1)     Vapor Pressure   Not established.     Vapor density   < 1 (air = 1)     Specific Gravity   0.87 @ 15°C     Water Solubility   Not soluble.     Partition Coefficient   >1	d		
Cup     Evaporation Rate   < 1 (BuAc = 1)     Vapor Pressure   Not established.     Vapor density   < 1 (air = 1)     Specific Gravity   0.87 @ 15°C     Water Solubility   Not soluble.     Partition Coefficient   >1	d		
Evaporation Rate     < 1 (BuAc = 1)       Vapor Pressure     Not established.       Vapor density     < 1 (air = 1)       Specific Gravity     0.87 @ 15°C       Water Solubility     Not soluble.       Partition Coefficient     >1			
Vapor Pressure     Not established.       Vapor density     < 1 (air = 1)       Specific Gravity     0.87 @ 15°C       Water Solubility     Not soluble.       Partition Coefficient     >1			
Vapor density < 1 (air = 1)   Specific Gravity 0.87 @ 15°C   Water Solubility Not soluble.   Partition Coefficient >1			
Specific Gravity     0.87 @ 15°C       Water Solubility     Not soluble.       Partition Coefficient     >1			
Water Solubility     Not soluble.       Partition Coefficient     >1	< 1 (air = 1)		
Partition Coefficient >1	0.87 @ 15°C		
	Not soluble.		
Auto Imitian Tama antima Not available	>1		
Auto-Ignition Temperature Not available	Not available		
NLGI Grade 2			
Thickener Type Aluminum Complex			
Base Oil Type USP Grade White Mineral Oil	USP Grade White Mineral Oil		
Viscosity 112 cst @ 40°C			
Dropping Point >450°F (>232.2°C)			
Temperature Range0°F (-18°C) to 300°F (149°C)			
4-Ball Weld Load >250 kg			
Timken OK Load 40 lb			
Water Washout <1%			
Copper Corrosion Not available.	Not available.		

# DIRECTIONS

For use in areas where incidental food contact may occur or in applications where clean, non-toxic lubricants are preferred. Apply either manually or by a suitable applicator. It is recommended that LPS® DETEX® FOODLUBE® Bearing Grease not be mixed with other greases. Acceptable for use in Canadian Food Processing Establishments. Do not add directly to food.

# HANDLING

Observe good industrial hygiene practices. Wash hands after handling.

## STORAGE

Store away from incompatible materials.

#### DISPOSAL

Dispose of waste and residues in accordance with local authority requirements.

# **AVAILABLE PRODUCTS**

Part No.					
US	Canada	Net Contents	Container Type	Units/Case	Approximate Case
					Weight
70114	C70114	14.1 oz / 400 g	cartridges	30	32 lbs
70155		55 gal / 400 lbs	drum	1	450 lbs

#### METAL DETECTION DETAILS

- Detection limits for a particular machine depend on a variety of factors including line speed, contaminant placement and orientation, iron fortification (i.e.; flour), wet mode vs. dry mode, fragment size, aperture size, etc. It is the responsibility of the end- user to determine the detection limits of the appropriate DETEX® component for the individual line set up and for the particular food product being inspected.
- Metal and X-ray detection limits for plastic components (above) are based on whole components. Partial plastic and scouring pad components may not be detectable due to detector limitations, partial component size, malfunctioning equipment and/or the type of food product undergoing processing. Scouring pad not X-ray detectable.
- ITW Pro Brands recommends that all components be tested prior to implementation (separately and included in the processed food product) and/or consult your specific metal detector equipment manufacturer directly.
- 4. Product shelf life, warranty, and material safety data sheets are available at www.itwprobrands.com. ITW Pro Brands is not responsible for use of this product inconsistent with its instructions and warnings.
- 5. ITW Pro Brands is not responsible for failure to detect components due to detector limitations and/or detector malfunctions. Refer to the metal detector manufacturer's design limitations, instructions, and warnings regarding the use, limitations, and proper maintenance of the equipment.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved