



# LPS<sup>®</sup> MAX Orange Degreaser

## Low VOC Solvent



### FEATURES

- Excellent for removing grease, grime, oil, and adhesives
- High solvent strength for instant cleaning action
- Controlled evaporation, leaves little residue
- Low VOCs (Volatile Organic Compounds), compliant in all 50 states
- Does not contain chlorinated or brominated solvents
- Excellent alternative to Methyl Ethyl Ketone (MEK), Toluene, and/or Xylene
- Meets VOC regulations of CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Not a Hazardous Air Pollutant (HAP)
- No ozone depleting compounds (ODC)
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

### APPLICATIONS

- Bearings
- Chains
- Controls
- De-Energized Cable Connections
- Forklifts
- Gears
- Hand & Power Tools
- Heavy Equipment
- Machinery
- Motors
- Pulleys

### PROPERTIES

<b>Appearance / Physical State</b>	Gas/Aerosol
<b>Odor</b>	Acetone/Orange
<b>Percent Volatile</b>	100%
<b>Flammability</b>	Flammability limit - lower (%) 2.5% Flammability limit - upper (%) 12.8%
<b>Propellant</b>	Carbon dioxide
<b>VOC Content</b>	9.45% per US State and Federal Consumer Product Regulations
<b>Color</b>	Clear water-white
<b>Flash Point</b>	-4.0 °F (-20.0 °C) Tag Closed Cup (estimated)
<b>Density</b>	6.70 lb/gal @ 25°C
<b>Evaporation Rate</b>	0.2 BuAc
<b>Viscosity</b>	Not Available
<b>Specific Gravity</b>	0.81 @ 20°C

### DIRECTIONS

Spray metal parts and equipment and allow to run off. For a directed stream, place the flip straw in the upright position. For a broad area coverage, place the flip straw in the downward position. Remove excess with a soft wipe or allow to air dry. If equipment is still dirty or greasy, repeat procedure. Test rubber and plastic surfaces for compatibility. After degreasing is complete protect equipment with LPS<sup>®</sup> MAX 1<sup>®</sup> Greaseless Lubricant or LPS<sup>®</sup> MAX 2<sup>®</sup> Heavy-Duty Lubricant.

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### STORAGE

Level 2 Aerosol.  
Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
97320	15 oz	aerosol	12	15



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved