



# LPS<sup>®</sup> MAX ZeroTri<sup>®</sup> Fast-Acting Heavy Duty Degreaser



## FEATURES

- Fast acting solvent penetrates petroleum soils to instantly dissolve oil, grease, and grime
- Ideal for degreasing parts and equipment
- No ozone depleting chemicals
- Leaves no residue, no rinsing required
- Does not contain chlorinated or brominated solvents
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

## APPLICATIONS

- Air Compressors
- Bearings
- Chains
- Construction Equipment
- Conveyor Systems
- Cranes
- Forklifts
- Gears
- Printing Presses
- Pulleys

## SPECIFICATIONS AND APPROVALS

- NSF International, C1

## PROPERTIES

<b>Appearance / Physical State</b>	Gas/Aerosol
<b>Color</b>	Colorless. Clear.
<b>Odor</b>	Ether-like. Fruity.
<b>Melting / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	> 132.8 °F (> 56 °C)
<b>Flash Point</b>	1.4°F (-17.0 °C) Tag Closed Cup
<b>Evaporation Rate</b>	> 1 (BuAc = 1)
<b>Flammability</b>	Flammability limit - lower (%) 1.2% Flammability limit - upper (%) 12.8%
<b>Vapor Pressure</b>	> 75 mm Hg @ 20°C
<b>Vapor Density</b>	~ 3 (air = 1)
<b>Water Solubility</b>	35% w/w
<b>Percent Volatile</b>	100%
<b>Specific Gravity</b>	0.74 - 0.76 @ 20°C
<b>VOC Content</b>	62.4 % per U.S. State and Federal Consumer Product Regulations
<b>Propellant</b>	Carbon dioxide

## DIRECTIONS

Spray metal parts and equipment and allow to run off. For a directed stream, place the flip straw in the upright position. For a broad area coverage, place the flip straw in the downward position. Remove excess with a soft wipe or allow to air dry. If equipment is still dirty or greasy, repeat procedure. Test rubber and plastic surfaces for compatibility. After degreasing is complete protect equipment with LPS<sup>®</sup> MAX 1<sup>®</sup> Greaseless Lubricant or LPS<sup>®</sup> MAX 2<sup>®</sup> Heavy-Duty Lubricant.

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
93520	15 wt oz / 425 g	aerosol	12	15 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved