



Magnum

Premium Lubricant with PTFE



FEATURES

- Does not contain silicone
- Safe to use on most surfaces
- Flash point of 175°F (79°C)
- Penetrates and protects metal against rust and corrosion
- Ideal for both regular and extreme conditions
- High performance lubricant with PTFE additives
- Extends equipment life
- Nonfood Compounds Program Listed Category Code: H2 Registration #128980 (Aerosol); #128981 (Bulk)

APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Dies, Bits & Fasteners
- Engines & Electric Motors
- Hoists, Lifts & Draglines
- Metal Parts & Hand Tools
- Parts in Storage
- Production & Transportation Equipment
- Pulleys and rollers
- Slides and tracks

SPECIFICATIONS AND APPROVALS

- NSF International, H2 (Aerosol)
- NSF International, H2 (Bulk)

PROPERTIES

Appearance / Physical State	Aerosol: Gas Bulk: Liquid
Odor	Mild. Sweet.
Melting / Freezing Point	Not established
Boiling Point / Range	383°F (195°C)
Vapor Pressure	< 0.05 mm Hg @ 20°C
Partition Coefficient	< 1
Percent volatile	Not established
Flammability	Lower: 0.6% Upper: 7%
Propellant	Carbon Dioxide
VOC Content	Aerosol: 2.9%; Bulk: 3.0% per State & Federal Consumer Product Regulations
Color	Brown
Flash Point	174.2°F (79.0°C) Tag Closed Cup - dispensed liquid
Density	Not available.
Evaporation Rate	< 0.1 BuAc
Vapor density	4.7 (air = 1)
Auto-Ignition Temperature	> 442.4°F (> 228°C)
Viscosity	< 7 cSt @ 25°C
Specific Gravity	0.85 - 0.87 @ 20°C
Temperature Range	-60°F - 300°F (-51°C - 149°C)
4-Ball Weld Load	Not available.

DIRECTIONS

Shake well before using. Apply on clean surface when possible. Spray in even coats and reapply as needed.

HANDLING

DO NOT spray into or around ignition sources. DO NOT allow material to come in contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F and 120°F (4.4°C and 49°C). Protect from freezing. Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
00616	C00616	11 wt oz / 312 g / 358 mL	aerosol	12	12 lbs
00605		5 gal / 18.93 L	pail	1	41 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved